

Technical Specifications


Model	CBK 8a	CBK 16aH	CBK 16a	CBK 35a	CBK 70a	CBK 100a
Maximum capacity	8lb/4000g	16lb/8000g	16lb/8000g	35lb/16kg	70lb/32kg	100lb/48kg
Readability	0.0002lb/0.1g	0.0002lb/0.1g	0.0005lb/0.2g	0.001lb/0.5g	0.002lb/1g	0.005lb/2g
Tare range	Full	Full	Full	Full	Full	Full
Repeatability (S.D.)	0.1g	0.1g	0.2g	0.5g	1g	2g
Linearity (±)	0.2g	0.2g	0.4g	1g	2g	4g
Platform	8.9 x 10.8" / 225 x 275mm					

General Specifications

Units of measurement	Gram (g), Kilogram (kg), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz)
Typical stabilisation time	2 Sec
Interface	RS-232 bi-directional Interface
Calibration	Automatic external
Display	6 digits LCD displays
Battery	Internal Rechargeable battery up to 90 hours
Power supply	Mains power cord / internal rechargeable battery
Real-time clock	Real-time clock
Housing	ABS Plastic
Overall dimensions (wxdxh)	12.4 x 14 x 4.3" / 315 x 355 x 110mm
Net weight	9lb

Key Accessories

- In-use Cover
- In-Use Cover pack of 10
- Weigh Below Hanger (factory fitted)
- RS-232 to PC Cable
- RS-232 to USB Interface Cable (must be ordered in conjunction with the appropriate RS232 cable)
- AdamDU - Data Collection Program
- Hard Carry Case with Lock
- ATP Thermal Printer
- Thermal Paper For Adam ATP (10 pack)



Adam Equipment - offices worldwide

www.adamequipment.com