



Magnehelic® Gage Options



LED Setpoint Indicator



Adjustable Signal Flag



Transparent Overlay



Mirrored Scale Overlay



Integrated Mounting Plate



LED Setpoint Indicator

Bright red LED on right scale shows when setpoint is reached. Field adjustable from gage face, unit operates on 12-24 VDC. Setpoint indicator option comes with medium pressure (MP) bezel.

Note: 4-13/16" hole for flush mounting.

To order add suffix -SP

Adjustable Signal Flag

Integral with plastic gage cover. Available for most models except those with medium or high pressure construction. Can be ordered with gage or separate.

To order add suffix -ASF

Transparent Overlays

Furnished in red, yellow, or green to highlight and emphasize critical pressures.

To order add suffix -R (Red)

To order add suffix -Y (Yellow)

To order add suffix -G (Green)

Mirrored Scale Overlay

A Mirrored Scale Overlay is also available to assist in reducing parallax error.

To order add suffix -M

Integrated Mounting Plate

Furnished with attached surface mounting plate.

To order add suffix -AHU1

Furnished with attached surface mounting plate and including A-481 installer kit (2 plastic static pressure tips and 7' of PVC tubing).

To order add suffix -AHU2

MODELS FOR HIGH STATE PRESSURE APPLICATIONS

Medium Pressure Option: for pressures to 35 psig.

To order add suffix -MP

High Pressure Option: for pressures to 80 psig.

To order add suffix -HP

OPTIONAL BEZELS

Stainless Steel Bezel Option:

304 Stainless Steel Electro polished Ra 16 finished bezel for the Magnehelic® is now available.

To order add suffix -SB

Chrome Bezel Option:

A Chrome Plated Aluminum Bezel is now available on the Magnehelic® gage for an aesthetically pleasing finish when mounting on metal surfaces such as control panels.

To order add suffix -CB

OPTIONS — To order, add suffix: I.E. 2001-ASF

LT, Low Temperatures to -20°F (-28°C)

NIST, NIST traceable calibration certificate

FC, factory calibration certificate