



Speed, Performance, Value - Perfect Balance

- 4 Weighing units (kg, lb:oz, lb, oz)
- Simple 4 button operation
- Hold function
- Full range tare
- Zero Tracking
- Large backlit LCD display
- Wall mount bracket
- Large stainless steel pan
- Modern low profile design
- Splashproof to protect from accidental spills
- Precision load cell technology
- Colour coded, sealed keypad
- RS-232 bi-directional interface
- Low battery indication
- Auto sleep / power down function to save battery life
- Battery power (6 x AA Batteries)
- AC Adapter
- Weighing
- Animal / dynamic weighing



Technical Specifications

| Model | CPWplus 6 | CPWplus 15 | CPWplus 35 | CPWplus 75 | CPWplus 150 | CPWplus 200 |
|-----------------------------|----------------------------|------------|------------|------------|-------------|-------------|
| Maximum capacity | 13lb/6000g | 33lb/15kg | 75lb/35kg | 165lb/75kg | 330lb/150kg | 440lb/200kg |
| Readability | 0.005lb/2g | 0.01lb/5g | 0.02lb/10g | 0.05lb/20g | 0.1lb/50g | 0.1lb/50g |
| Tare range | Full | Full | Full | Full | Full | Full |
| Repeatability (S.D.) | 2g | 5g | 10g | 20g | 50g | 50g |
| Linearity (±) | 4g | 10g | 20g | 40g | 100g | 100g |
| Platform size | 11.8 x 11.8" / 300 x 300mm | | | | | |

The same models are available with additional display on a Pillar as series denoted with 'P'.

General Specifications

| | |
|-----------------------------------|--|
| Units of measurement | Kilogram (kg), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz) |
| Typical stabilisation time | 2 Sec |
| Interface | RS-232 bi-directional Interface |
| Calibration | Automatic External with user selectable calibration mass |
| Display | LCD with minimum 22mm digits with weight legends for kg, lb, oz and low battery, stable, zero, net weight and hold symbols, as well as ability to display lb and oz together |
| Power supply | 6 AA size non-rechargeable batteries in a compartment located in the base or 12VAC 150mA from external adapter |
| Operating temperature | 32°F - 104°F |
| Housing | Indicator- Aluminium, Platform- Mild Steel base and stainless steel platform |
| Overall dimensions (wxdxh) | 11.8 x 11.8 x 2" / 300 x 300 x 50mm |
| Dimensions notes | Indicator: 220 x 95 x 43mm (w x d x h) |

Key Accessories

- Hard Carry Case with Lock
- AdamDU - Data Collection Program
- RS-232 to PC Cable
- RS-232 to USB Interface Cable (must be ordered in conjunction)
- ATP Thermal Printer
- Thermal Paper For Adam ATP (10 pack)



Adam Equipment - offices worldwide

www.adamequipment.com