

## Technical Specifications

Model	PW 124	PW 184	PW 254
Maximum capacity	120g	180g	250g
Readability	0.0001g	0.0001g	0.0001g
Tare range	Full	Full	Full
Repeatability (S.D.)	0.00015g	0.0002g	0.0002g
Linearity ( $\pm$ )	0.0002g	0.0002g	0.0002g
Pan size	3.5" &Oslash; / 90mm &Oslash; ;		

## General Specifications

Units of measurement	Gram (g), Milligram (mg), Carat (ct), Ounce (Oz), Dram (d), Grain (GN), Troy Ounce (Ozt), Pennyweight (dWt), Momme (MM), TaelS Hk. (TL.H), TaelS S. (TL.S), TaelS T. (TL.T), Tical (ti), Newton (N), Tola (T), Custom unit
Interface	Bi-directional RS-232 (Standard)
Calibration	Calibration with internal mass. Alternatively the user can chose to calibrate using an external mass
Display	Backlit LCD with dual digits (24 mm high) and capacity tracker
Power supply	15 VDC, 50/60 Hz, 800 mA (Input Voltage 100-240 V, 50/60 Hz)
Housing	Die cast aluminium housing with glass weighing chamber
Draught shield	Supplied as standard (factory fitted)
Draught shield dimensions	202x158x215mm
Overall dimensions (wxdxh)	10.1 x 20.6 x 10.8" / 256 x 524 x 275mm

## Key Accessories

- Anti-Vibration Table
- Density Determination Kit
- Security Lock and Cable
- Dust Cover
- RS-232 to USB Interface Cable (must be ordered in conjunction
- RS-232 to PC Cable
- AdamDU - Data Collection Program
- Below Balance Hanger
- In-use Cover
- ATP Thermal Printer
- ASTM O - 100g calibration weight
- Thermal Paper For Adam ATP (10 pack)



Adam Equipment - offices worldwide

[www.adamequipment.com](http://www.adamequipment.com)