

## Technical Specifications

Model	CPWplus 35W	CPWplus 75W	CPWplus 150W	CPWplus 200W
Maximum capacity	75lb/35kg	165lb/75kg	330lb/150kg	440lb/200kg
Readability	0.02lb/10g	0.05lb/20g	0.1lb/50g	0.1lb/50g
Tare range	Full	Full	Full	Full
Repeatability (S.D.)	10g	20g	50g	50g
Linearity (±)	20g	40g	100g	100g
Pan size	19.7 x 19.7" / 500 x 500mm			

## General Specifications

Tare functions	Full
Units of measurement	Pound (lb), Kilogram (kg), Ounce (Oz), Pound-Ounce (lb-oz)
Typical stabilisation time	2 - 3 Sec
Calibration	Automatic external
Display	22mm Backlit LCD digits
Battery	Internal Rechargeable Battery
Power supply	12 VDC, 500 mA Power Supply
Overall dimensions (wxdxh)	19.7 x 19.7 x 1.6" / 500 x 500 x 40mm
Dimensions notes	Indicator: 220 x 95 x 43mm (w x d x h)
Net weight	27.4lb

## Key Accessories

- RS-232 to PC Cable
- RS-232 to USB Interface Cable (must be ordered in conjunction with the appropriate RS232 cable)
- AdamDU - Data Collection Program
- ATP Thermal Printer
- Thermal Paper For Adam ATP (10 pack)



Adam Equipment - offices worldwide

[www.adamequipment.com](http://www.adamequipment.com)