





Speed, Performance, Value - Perfect Balance

- 3 Weighing units (g, lb, oz)
- Full range tare
- Zero Tracking
- Large easy to read LCD display
- Overload protection
- Colour coded, sealed keypad
- Lightweight and portable
- Simple user-friendly operation
- Precision load cell technology
- Splashproof to protect from accidental spills
- External calibration
- Battery power (6 x AA Batteries)
- Low battery indication
- Auto sleep / power down function to save battery life
- AC Adapter
- Weighing



Technical Specifications

Model	DCT 201	DCT 2000	DCT 5000
Maximum capacity	200g	2000g	5000g
Readability	0.1g	1g	2g
Repeatability (S.D.)	0.1g	1g	2g
Linearity (\pm)	0.2g	2g	4g
Units of measurement	Gram (g), Ounce (Oz)	Gram (g), Ounce (Oz), Pound (lb)	
Pan size	5.7 x 5.7" / 145 x 145mm		

General Specifications

Typical stabilisation time	2 Sec
Operating temperature	32°F - 104°F
Power supply	12VAC 150mA adapter / 6 x AA batteries
Calibration	Automatic External
Display	Large Display
Overall dimensions (wxdxh)	8.2 x 5.8 x 1.6" / 208 x 147 x 40mm



Adam Equipment - offices worldwide

www.adamequipment.com