




Speed, Performance, Value - Perfect Balance

- Up to 12 Weighing units (including one custom unit)
- Date and time
- Full range tare
- Zero Tracking
- Multilingual display
- Large backlit display with dual text prompts
- Capacity tracker
- Large stainless steel pan
- Solid metal housing
- Overload protection
- Lock down mounting slot for Kensington® type lock and cable
- Non-slip adjustable levelling feet
- Colour coded, sealed keypad
- Dual tare keys
- Removable draft shield supplied on 0.001g readabilities
- Modern low profile design
- RS-232 bi-directional interface
- GLP print outs
- External calibration
- Rechargeable battery
- DC Adapter
- Auto sleep / power down function to save battery life
- Dust Cover not available on PGL10001, PGL20001 and PGL30001
- Weighing
- Parts counting
- Percentage weighing
- Check weighing
- Density determination
- Below balance weighing



Technical Specifications

Model	PGL 203	PGL 303	PGL 2002	PGL 3002	PGL 4001	PGL 6001	PGL 8001	PGL 1000 1	PGL 1200 1	PGL 1500 1	PGL 2000 1	PGL 3000 1
Maximum capacity	200g	300g	2000 g	3000 g	4000 g	6000 g	8000 g	10kg	12kg	15kg	20kg	30kg
Readability	0.001 g	0.001 g	0.01g	0.01g	0.1g	0.1g	0.1g	0.1g	0.1g	0.1g	0.1g	0.1g
Repeatability (S.D.)	0.002 g	0.003 g	0.02g	0.03g	0.2g	0.2g	0.2g	0.2g	0.2g	0.2g	0.2g	0.2
Linearity (±)	0.004 g	0.006 g	0.04g	0.06g	0.2g	0.2g	0.2g	0.4g	0.4g	0.4g	0.4g	0.4g
Units of measurement	Gram (g), Kilogram (kg), Milligram (mg), Carat (ct), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz), Grain (GN), Troy Ounce (Ozt), Pennyweight (dWt), Newton (N), Custom unit											-
Pan size	5.7 x 4.9" / 145 x 125mm		7.6 x 7.6" / 192 x 192mm					15.7 x 11.8" / 400 x 300mm	7.6 x 7.6" / 192 x 192mm		15.7 x 11.8" / 400 x 300mm	15.7 x 11.8" / 400 x 300mm

General Specifications

Typical stabilisation time	2-3 Sec
Power supply	12VDC 800mA AC adaptor and rechargeable battery pack
Calibration	Automatic External
Display	Backlit LCD display with dual digits and capacity tracker
Overall dimensions (wxdxh)	9.9 x 14.1 x 4.1" / 251 x 358 x 104mm
Dimensions notes	400 x 460 x 100mm (PGL10001 & PGL20001)

Key Accessories

- Density Determination Kit (mg models only)
- RS-232 to USB Interface Cable (must be ordered in conjunction)
- Security Lock and Cable
- Anti-Vibration Table
- Below Balance Hanger
- In-use Cover
- Dust Cover
- AdamDU - Data Collection Program
- RS-232 to PC Cable
- ASTM 3 - 10000g (2 x 5000g) calibration weights
- ASTM 2 - 1000g calibration weight
- ASTM 4, 2000g calibration weight
- ASTM 3 - 5000g calibration weight
- ATP Thermal Printer
- Thermal Paper For Adam ATP (10 pack)
- ASTM 1, 200g calibration weight



Adam Equipment - offices worldwide

www.adamequipment.com