





Speed, Performance, Value - Perfect Balance

- Date and time
- Selectable multi-language text for printing
- Preset counting to a value
- Large backlit LCD display
- Overload protection
- Non-slip adjustable levelling feet
- Large stainless steel platform
- Pillar mounted
- Full colour coded keypad with numeric entry
- Precision load cell technology
- Simple user-friendly operation
- Splashproof to protect from accidental spills
- Easy access to the rechargeable battery
- RS-232 bi-directional interface
- External calibration
- Auto sleep / power down function to save battery life
- Low battery indication
- Mains Power Cord
- Weighing
- Parts counting
- Check counting



Technical Specifications

Model	GFC 165a	GFC 330a	GFC 660a
Maximum capacity	165lb/75kg	330lb/150kg	660lb/300kg
Readability	0.01lb/5g	0.02lb/10g	0.05lb/20g
Linearity (±)	0.02lbb / 10g	-	-
Pan size	15.7 x 19.7" / 400 x 500mm		
Net weight	27.5lbb	-	27.5lb

General Specifications

Typical stabilisation time	2-3 Sec
Power supply	Mains power cord / internal rechargeable battery
Calibration	Automatic External
Display	Large LCD backlit display
Housing	Indicator: ABS Plastic Top pan: Grade 304 stainless steel Base: Painted mild steel
Overall dimensions (wxdxh)	33.9 x 15.7 x 24.4" / 860 x 400 x 620mm

Key Accessories

- RS-232 to PC Cable
- AdamDU - Data Collection Program
- In-use Cover
- RS-232 to USB Interface Cable (must be ordered in conjunction)
- ATP Thermal Printer
- Thermal Paper For Adam ATP (10 pack)



le)



Adam Equipment - offices worldwide

www.adamequipment.com