

Technical Specifications

Model	GBC 35a	GBC 70a	GBC 130a
Maximum capacity	35lb/16kg	70lb/32kg	130lb/60kg
Readability	0.001lb/0.5g	0.002lb/1g	0.005lb/2g
Repeatability (S.D.)	0.002lb / 1g	0.002lb / 1g	0.01lb / 4g
Linearity (±)	0.002lb / 1g	0.002lb / 1g	4g
Typical stabilisation time	2-3 Sec	-	2-3 Sec
Pan size	11.8 x 15.7" / 300 x 400mm		

General Specifications

Power supply	Mains power cord / internal rechargeable battery
Calibration	Automatic External
Display	Large LCD backlit display
Overall dimensions (wxdxh)	11.8 x 20.5 x 26.8" / 300 x 520 x 680mm
Dimensions notes	Shipping Weight: 16Kg Dims: 90 x 46 x 21cm

Key Accessories

- RS-232 to USB Interface Cable (must be ordered in conjunction with the appropriate RS232 cable)
- AdamDU - Data Collection Program
- In-use Cover
- RS-232 to PC Cable
- ATP Thermal Printer
- Thermal Paper For Adam ATP (10 pack)



Adam Equipment - offices worldwide

www.adamequipment.com