



Speed, Performance, Value - Perfect Balance

- BMI-Body mass index
- Wheels to allow easy movement
- Enhanced Height rod as standard (measures up to 60-212 cm)
- Robust metal housing
- Anti-slip platform
- Large red LED display
- Colour coded, sealed keypad
- External calibration
- Hold function
- Full range tare
- DC Adapter
- Overload protection
- Rechargeable battery / mains adapter supplied as standard
- 2 weighing units (kg, lb)
- Precision load cell technology
- Simple user-friendly operation
- RS-232 interface
- Weighing
- Measuring height



Technical Specifications

Maximum capacity	660lb/300kg
Readability	0.1lb/50g
Pan size	14.8 x 10.8" / 375 x 275mm

General Specifications

Model	MDW 300L
Power supply	Internal re-chargeable 6V battery / 220 VAC through adapter
Calibration	External
Display	LCD
Housing	Metal, Indicator: ABS Plastic
Overall dimensions (wxdxh)	21.1 x 10.8 x 37" / 535 x 275 x 940mm
Height range	60cm - 212cm
Division of measurement	0.1cm

Key Accessories

- RS-232 to USB Interface Cable (must be ordered in conjunction with the
- ATP Thermal Printer
- RS-232 to PC Cable
- Thermal Paper For Adam ATP (10 pack)
- AdamDU - Data Collection Program



Adam Equipment - offices worldwide

www.adamequipment.com