

PTM Drum / Wheelchair Platforms



The PTM low profile platform is ideal for drums and wheelchairs. The easy access ramps on both sides offers smooth transitions from the floor to the weighing platform and the diamond checked platform offers a durable weighing area. With handles and wheels for easy portability the PTM can be used where it's needed in a warehouse or medical facility.

The PTM is available with the GK indicator or AE 401 indicator to give a range of different features and functions. The long cable lets the indicator be placed where it is needed out of the way of the platform for easy viewing. The GK indicator allows for a numeric tare value to be entered where the AE 401 is IP65 sealed for dust and water environments.

With over three decades of experience in the production of weighing equipment you can trust Adam for quality products that offer a range of features designed for a many different applications



AE ADAM[®]
PERFECT BALANCE
Speed, Performance, Value


PTM Series

PTM platform scale feature a low profile design for easy loading and unloading. The range incorporates a non-slip checkered plate for added grip.

Heavy duty rubber feet support the four loadcells ensuring quality and longevity of the bases.

Features

- Adjustable levelling feet
- 4 loadcell construction
- 10 feet of loadcell cable
- Heavy duty rubber feet
- Handles and wheels for portability



GK Indicator

With a number of weighing modes and units the GK indicators can be adapted to a wider range of applications. A large backlit display is easy to read with a capacity tracker to help protect from overloading and the colored LED indicators are ideal for check weighing applications to measure underweight, overweight and acceptable limits. With standard RS-232 interface for computers and printers, rechargeable battery and AC adapter powered, and full numerical keypad, the GK offers the most value for an indicator.

Features

- Full tare range
- Accessible internal rechargeable battery
- Large backlit LCD display with capacity tracker
- Battery operation with auto-off to save battery life
- Check weighing LED lights to show acceptable limits
- Bi-directional RS-232 output for connection to computers and printers



AE 401 Indicator

The AE 401 is a multi-purpose wash-down weighing indicator that can be used for a wide range of applications. With a large easy-to-read backlit LCD display this indicator provides faster readings. The AE 401 offers digital filters, memory accumulation, tare, display hold, an RS-232 interface, plus an internal rechargeable battery and an AC adapter included.

Features

- Hold Function
- Quick and easy to configure through keypad
- Full range tare
- Backlit LCD display
- Wall mount bracket
- Supports up to four 350 ohm loadcells
- Uni-directional RS-232 interface
- External calibration



Technical Specifications

PTM Series

Model	Maximum Scale Capacity (lb/kg)	Platform Size (in/mm)	Height (in/mm)	Net Weight (lb/kg)	Cable	Construction
PTM	1100lb / 500kg	33in x 31in 820mm x 780mm	2.7in / 70mm	74lb / 33.5kg	10ft / 3m long	Mild Steel

GK Indicators

Model	Sensitivity	Loadcells	Zero input range	Signal Range	Weighing Units	Readability
GK	Up to 1:30,000	Up to 4 x 350ohm loadcells	0 - 10mV	0 - 40mV	g, kg, lb, oz, lb:oz	Selectable

AE 401 Indicators

Model	Sensitivity	Loadcells	Zero input range	Signal Range	Weighing Units	Readability
AE 401	0.15uv/d	Up to 4 , 350 ohm loadcells – Minimum 87ohms, maximum 1120ohms	0- 10mv	0+40mv	lb / kg	Selectable

Accessories

- Item No. 8023 - Adam Printer
- Item No. 9665 - In-Use Cover for GK
- Item No. 9192 - Thermal replacement paper (5-pack)



www.adamequipment.com