

Calibrator/Manometer

The BETA Calibrators CALTool line is designed to give the technician laboratory-grade accuracy in a family of rugged, easy-to-use instruments.

The CALTool 32 Pressure Calibrator is available in several ranges — 200" H₂O, and 30, 100, 300, and 3,000 PSI. Operation of these calibrators is made easy through the use of a sealed membrane keypad with simple controls. When combined with a MECP-100 Hand Pump, the CALTool 32 Kit makes a great package to handle your pneumatic calibration requirements.





Features:

- High accuracy gauge or differential capability
- Rugged, dust tight, water-resistant case
- Isolated SS sensors on 300 PSI and 3,000 PSI units
- Easy to read Super-Twist LCD
- Intuitive controls make operation easy, even for infrequent users
- Powered by a common 9 Volt alkaline battery
- Supplied in full rubber boot

Specifications (1 year at 23 °C ±5 °C; % of reading unless otherwise noted)

Ranges -14.00 to 30.00 PSIG/PSID

-14.00 to 100.0 PSIG/PSID -14.00 to 300.0 PSIG -14.00 to 3000 PSIG

±200" H₂0

Accuracy 18 °C to 28 °C

 $\pm 200^{\circ}$ H₂O
 $\pm 0.05\%$ of FS, $\pm 0.03^{\circ}$ H₂O

 30 PSI
 $\pm 0.05\%$ of FS, ± 0.001 PSI

 100 PSI and 300 PSI
 $\pm 0.05\%$ of FS, ± 0.01 PSI

 3,000 PSI
 $\pm 0.05\%$ of FS, ± 0.1 PSI

Resolution

 ±200" H20
 0.01" H20

 30 PSI
 0.001 PSI

 100 PSI and 300 PSI
 0.01 PSI

 3,000 PSI
 0.1 PSI

Engineering Units
PSI, inH20, cmH20, mH20, mH20, FtH20, mBAR,

BAR, inHg, mmHg, cmHg, kPa, kg/cm², TORR, ATM $\pm 0.01\%$ FS/°C; 0 °C to 18 °C, and 28 °C to 50 °C

Maximum Overpressure 2x

Ports Two 1/8" FNPT

Media

30/100 PSI, 200" H₂O non-corrosive gas or liquids

300/3,000 PSI all media

Environmental

Temperature Stability

Operating temperature $0 \,^{\circ}\text{C}$ to $50 \,^{\circ}\text{C}$ Storage temperature $-20 \,^{\circ}\text{C}$ to $+60 \,^{\circ}\text{C}$

Mechanical

Dimensions, without boot 5.7" H x 3.5" W x 1.43" D (144.7 x 80.0 x 36.3 mm)

Weight 14 ounces (396 gms.)

Power Requirements 1, 9 Volt alkaline battery

Ordering Information

(Kit contains CALTool 32 Calibrator, MECP-100 Hand Pump (-12 to +100 PSI) fittings and connectors, rugged carrying case, test leads, 9 V battery, and NIST traceable certificate.)



MECP-100 Hand Pump (shown with optional in-line filter)

MECP-100 Hand Pump

The MECP-100 Hand Pump is a simple to use pressure and vacuum sorce for calibrating process control instrumentation. An optional in-line filter is available for applications where contaminants may enter the pump.