

Smart Tools – VAC set

testo 405i thermal anemometer
testo 410i vane anemometer
testo 605i thermohygrometer
testo 805i infrared thermometer
in the testo Smart Case

Compact pro measuring instrument from the Testo Smart Tools series for use with smartphones/tablets

For the measurement of air and surface temperature, humidity, air flow velocity and volume flow

Application-specific menus: Volume flow measurements in ducts and at outlets, identification of mould danger, easy image documentation incl. IR temperature measurement value and measurement spot marking; determination of the refrigeration/heating performance

Measurement data analysis as a table or graph

Measurement data analyzed and sent via testo Smart Probe App

Handy transport bag testo Smart Case



 **Bluetooth + App**

testo Smart Probe App for free download



The compact VAC set includes four App-controlled measuring instruments for important measuring tasks performed by VAC engineers: the testo 405i thermal anemometer, the testo 410i vane anemometer, the testo 605i thermohygrometer and the testo 805i infrared thermometer. In combination with a smartphone or tablet, it can be used to measure air and surface temperatures, air humidity, air flow velocities and volume flows in, on and around air conditioning plants and systems. Users can view their measuring values conveniently via the testo Smart Tools App installed on an end device. In the App, measurement parameters (such as humidity or

temperature) can be deleted, added, or their order altered, with just one click. It is also possible to change the displayed measurement parameters quickly. In addition to this, the App offers application-specific menus, incl. for the identification of mould risk; automatic calculation of volume flow at outlets/in ducts, by easy parameterization of the outlet/duct cross-section (dimensions and geometry). The measurement data log can then be emailed directly as a PDF or Excel file. In the handy testo Smart Case, the measuring instruments can be conveniently transported and are always to hand when they are needed.

Technical data/accessories

Smart Tools – VAC set


testo Smart Tools VAC set for servicing ventilation and air conditioning systems. Consists of: testo 405i, testo 410i, testo 605i, testo 805i, testo Smart Case (VAC), batteries, calibration protocol

Order no. 0563 0003




testo Smart Tools App

The App turns your smartphone/tablet into the display of up to 6 Testo Smart Tools at the same time. The operation of the measuring instruments as well as the display of the measurement values take place by Bluetooth via the Testo Smart Probe App on your smartphone or tablet – independently of the measurement location. In addition to this, you can use the App to create measurement reports, add photos and comments to these, and send them by e-mail. For iOS and Android.



	testo 405i	testo 410i	testo 605i	testo 805i
Sensor type	Hot wire	Vane	Humidity – capacitive	Infrared
Measuring range	0 to 20 m/s	0.4 to 30 m/s	0 to 100 %RH	-30 to +250 °C
Accuracy ±1 digit	±(0.5 m/s + 2.5 % of m.v.) (0 to 2 m/s) ±(0.15 m/s + 2.5 % of m.v.) (2 to 15 m/s)	±(0.2 m/s + 2 % of m.v.) (0.4 to 20 m/s)	±(1.8 %RH + 3 % of m.v.) at +25 °C (5 to 80 %RH)	±1.5 °C or ±1.5 % of reading 0 to +250 °C) ±2.0 °C (-20 to -0.1 °C) ±2.5 °C (-30 to -20.1 °C)
Resolution	0.01 m/s	0.1 m/s	0.1% RH	0.1 °C
Sensor type	NTC	NTC	NTC	
Measuring range	-20 to +60 °C	-20 to +60 °C	-20 to +60 °C	
Accuracy ±1 digit	± 0.5 °C	± 0.5 °C	±0.8 °C (-20 to 0 °C) ±0.5 °C (0 to +60 °C)	
Resolution	0.1 °C	0.1 °C	0.1 °C	
Compatibility	requires iOS 8.3 or newer / Android 4.3 or newer requires mobile end device with Bluetooth 4.0			
Storage temperature	-20 to +60 °C			
Operating temperature	-20 to +50 °C			-10 to +50 °C
Battery type	3 micro batteries AAA			
Battery life	15 hrs	200 hrs	250 hrs	30 hrs
Dimensions	200 x 30 x 41 mm	154 x 43 x 21 mm	243 x 30 x 24 mm	140 x 36 x 25 mm
	Telescope extendable to 400 mm	40 mm Vane diameter	100 mm probe shaft	
Optics				10:1
Laser marking				Diffraction optics (laser circle)
Emissivity				0.1 to 1.0 adjustable
Warranty	2 years			

Accessories	Order no.
ISO calibration certificate temperature, infrared thermometer, calibration points +60 °C; +120 °C, +180 °C	0520 0002
ISO calibration certificate humidity, calibration points 11.3 %RH and 75.3 %RH at +25°C	0520 0006
ISO calibration certificate humidity, calibration point 75.3 %RH at +25°C	0520 0096
ISO calibration certificate flow velocity, two-point calibration, calibration points 5 m/s and 10 m/s	0520 0094
ISO calibration certificate flow velocity, hot-wire/vane anemometer, Pitot tube; calibration points 5; 10; 15; 20 m/s	0520 0034
ISO calibration certificate flow velocity, hot-wire/vane anemometer, Pitot tube; calibration points 1; 2; 5; 10 m/s	0520 0004



1981 1794/msp/l/10.2015
Subject to change, including technical modifications, without notice.