

48 HOUR TURN AROUND

AUSTRALIA WIDE  
**SERVICE**



ABLE TO DETECT  
**UP TO 4 GASES**  
SIMULTANEOUSLY

ENQUIRE TODAY



# MULTI GAS DETECTOR

## BX616 PORTABLE MULTI-GAS DETECTOR

CO<sub>2</sub> and NH<sub>3</sub>


### FEATURES

- Small size and light-weight
- Simple operation with only 1 button
- Adjustable alarm levels for toxic gases
- Self protection for combustible gas sensor against high concentration
- Battery low voltage alert
- Confidence beep
- Self-test after power on
- Self-diagnostic and self-correction function

### APPLICATION

Steelworks, petrochemical plant, oil industry, shipbuilding yard, sewage treatment plant, mine, power supply, confined spaces etc.


BX616 is a multi-gas detector which can determine the combustible gases, O<sub>2</sub>, CO and H<sub>2</sub>S gases in the air. It's functional and watertight design (IP 66) incorporate a Bump proof, rubberized housing to meet the toughest requirement of harsh environment like underground tunnels, mines etc.



### APPEARANCE

- |                    |                                 |
|--------------------|---------------------------------|
| 1. Alarm Indicator | 6. Calibration cap fasten hole  |
| 2. Button          | 7. Hand strap                   |
| 3. Sensor channel  | 8. Alligator clip               |
| 4. Display screen  | 9. Label                        |
| 5. Buzzer          | 10. Charging/Communication port |

### SPECIFICATION

Measuring gas	O2	CO	H2S	Combustible	Working Temperature	Toxic gases: -20°C~50°C Combustible: -40°C~70°C
Measuring range	0-25% VOL	0-500ppm	0-100ppm	0-100%LEL		
Sensor type	Electrochemical			Catalytic	Working humidity	<95%RH (no condensation)
Measuring time	Diffuse naturally				Housing	Rubber enclosure
Response time	T <sub>90</sub> <30s				Standard accessories	Operation manual, calibration cap, charger, screwdriver, USB Cable
Display	LCD screen					
Audible	≥80db at 1m				Dimensions & weight	120mm*68mm*30mm, about 220g
Alarm method	Visual, audible and vibration signals				Ingress protection	IP66
Battery	DC3.7V 1800mAh Lithium battery				Ex grade	 II 2G Ex ia IIC T4 Ga or II 2G Ex db ia IIC T4 Gb
Operating life	≥8h per charge (Charging time: 4-6h)					
Event log	2000 events					

[www.hkcalibrations.com.au](http://www.hkcalibrations.com.au)

**1300 309 881**

THE LEADER IN CALIBRATION  
**HK CALIBRATION**  
TECHNOLOGIES PTY LTD

Calibrations scope ISO 17025-2017 & 9001-2015